

These data should be used to confirm that a specific building is accurately represented by the building set contained at this terminal node.


Terminal Node Description

COMPARISON TO TOTAL DATABASE:


- 100% steel frame with infill model building type versus 7% for the total database.
- 80% seismic zones 2 and 3 versus 43% for the total database.
- 60% institutional/educational occupancy classification versus 50% for the total database.
- 43% masonry cladding versus 20% for the total database.
- 18% historic buildings versus 9% for the total database.
- In this node, 50% damage control and 50% life safety performance objective.
- In this node, 30% seismic zone 2 and 50% seismic zone 3.

Cost Data

Structural Cost per Square Foot Probability Density Function for All Buildings in Node



Building & Site Characteristics



CODE	DESCRIPTION
C1	Concrete Moment Frame
C2	Concrete Shear Wall
C3	Concrete Frame with Infill Walls
PC1	Precast Concrete Tilt Up Walls
PC2	Precast Concrete Frame w/ Concrete Shear Walls
RM1	Reinforced Masonry w/ Metal or Wood Diaphragms
RM2	Reinforced Masonry w/ Precast Concrete Diaphragm
S1	Steel Moment Frame
S2	Steel Braced Frame
S3	Steel Light Frame
S4	Steel Frame w/ Concrete Walls
S5	Steel Frame w/ Infill Walls
URM	Unreinforced Masonry
W1	Wood Light Frame
W2	Wood (Commercial or Industrial)
CODE	DESCRIPTION
Assem.	Assembly
Com/Off	Commercial/Office
F/Ind/W	Factory/Industrial/Warehouse
Inst/Ed	Institutional/Educational
R/M	Retail/Mall
NG	None Given
Other	Other
Park	Parking
Res	Residential

