

These data should be used to confirm that a specific building is accurately represented by the building set contained at this terminal node.


Terminal Node Description

COMPARISON TO TOTAL DATABASE:



- Average year built is 1976, versus 1944 for the average of the total database. All buildings in this node were built after 1969.
- 100% immediate occupancy performance objective versus 16% for the total database.
- 100% small buildings versus 28% for the total database. Buildings in this node are very small.
- 100% factory/industrial/warehouse occupancy classification versus 14% for the total database.
- 77% moderate rehabilitation (Rehab2) versus 15% for the total database.
- 54% seismic zone 3 versus 28% for the total database, and 8% seismic zone 4 versus 50% for the total database.
- In this node, 54% metal deck diaphragms and 38% wood diaphragms.

Cost Data

Structural Cost per Square Foot Probability Density Function for All Buildings in Node



Building & Site Characteristics



CODE	DESCRIPTION
C1	Concrete Moment Frame
C2	Concrete Shear Wall
C3	Concrete Frame with Infill Walls
PC1	Precast Concrete Tilt Up Walls
PC2	Precast Concrete Frame w/ Concrete Shear Walls
RM1	Reinforced Masonry w/ Metal or Wood Diaphragms
RM2	Reinforced Masonry w/ Precast Concrete Diaphragm
S1	Steel Moment Frame
S2	Steel Braced Frame
S3	Steel Light Frame
S4	Steel Frame w/ Concrete Walls
S5	Steel Frame w/ Infill Walls
URM	Unreinforced Masonry
W1	Wood Light Frame
W2	Wood (Commercial or Industrial)
CODE	DESCRIPTION
Assem.	Assembly
Com/Off	Commercial/Office
F/Ind/W	Factory/Industrial/Warehouse
Inst/Ed	Institutional/Educational
R/M	Retail/Mall
NG	None Given
Other	Other
Park	Parking
Res	Residential

Building & Site Characteristics (cont.)